

WHAT IS CLAIMED IS:

1. A finder apparatus which is used together with a photographing apparatus, comprising:

5 a finder configured to present an image of a subject so as to be visually recognizable by an operator; and

positioning marker presentation member configured to present a marker for positioning for setting relative positions of the photographing apparatus and an object for calibration to the finder so as to be visually recognizable by the operator, when the object for calibration including at least one of a known shape and a known surface attribute is photographed to acquire a parameter of a photographing optical system of the photographing apparatus.

2. The finder apparatus according to claim 1, wherein the photographing apparatus is a stereo photographing apparatus which photographs the subject from a plurality of points of sight.

20 3. The finder apparatus according to claim 1, wherein the finder includes an optical finder including a finder optical system configured to form an optical path to guide the image of the subject into operator's eyes.

25 4. The finder apparatus according to claim 1, wherein the positioning marker presentation member includes:

marker image production section configured to produce the image of the marker for positioning; and

image superimposition section configured to superimpose the image of the marker for positioning
5 produced by the marker image production section upon the subject image presented in the finder.

5. The finder apparatus according to claim 1, wherein the photographing apparatus includes an image pickup device configured to convert the subject image
10 formed by the photographing optical system into image data to output the image data, and

the finder includes an electronic finder configured to display an image obtained by reproduction of the image data output from the image pickup device.

15 6. The finder apparatus according to claim 5, wherein the positioning marker presentation member superimposes and displays the image of the marker for positioning upon an image corresponding to the subject image displayed in the electronic finder.

20 7. The finder apparatus according to claim 6, wherein the photographing apparatus further includes storage section configured to store the image data output from the image pickup device as photographed image data, and

25 the positioning marker presentation member does not present the marker for positioning, when the image obtained by the reproduction of the photographed image

data stored in the storage section is displayed in the electronic finder.

8. The finder apparatus according to claim 6,
wherein the photographing apparatus further includes
5 control section configured to calculate a difference
between a position of the image of the object for
calibration displayed in the electronic finder and that
of the marker for positioning, and

the positioning marker presentation member
10 displays description concerning photography in the
electronic finder based on a calculation result in the
control section.

9. The finder apparatus according to claim 8,
wherein the photographing apparatus further includes
15 input section configured to operate the photographing
apparatus, and

the positioning marker presentation member
switches display and non-display of the description
concerning the photography based on information input
20 via the input section.

10. The finder apparatus according to claim 1,
wherein the positioning marker presentation member
includes one of a member which is analogous to the
marker for positioning and a member including the
25 marker for positioning, and

the one of the member which is analogous to the
marker for positioning and the member including the

marker for positioning is disposed on an optical path of a light which guides the image of the subject into the operator's eyes to present the marker for positioning.

5 11. The finder apparatus according to claim 1, wherein the photographing apparatus further includes input section configured to operate the photographing apparatus, and

 the positioning marker presentation member
10 switches presentation and non-presentation of the marker for positioning based on the information input via the input section.

 12. The finder apparatus according to claim 1, wherein the positioning marker presentation member
15 allows the marker for positioning to blink.

 13. The finder apparatus according to claim 1, wherein the positioning marker presentation member does not present the marker for positioning during usual photographing.

20 14. The finder apparatus according to claim 1, wherein the positioning marker presentation member does not present the marker for positioning during photography for a purpose of obtaining three-dimensional information of the subject.

25 15. The finder apparatus according to claim 14, wherein the photography for the purpose of obtaining the three-dimensional information of the subject

includes photography in which a pattern is projected onto the subject.

16. The finder apparatus according to claim 1, wherein for the marker for positioning, at least one of
5 line segments, intersecting line segments, points, curves, intersecting curves and closed curves are disposed, and accordingly the marker for positioning indicates a closed region corresponding to a contour of the image of the object for calibration presented in
10 the finder in a state in which the relative positions of the photographing apparatus and the object for calibration are appropriately set.

17. The finder apparatus according to claim 16, wherein the marker for positioning indicates at least
15 a corner position of the closed region.

18. The finder apparatus according to claim 16, wherein the marker for positioning surrounds an outer edge of the closed region.

19. The finder apparatus according to claim 1, wherein for the marker for positioning, at least one of
20 line segments, intersecting line segments, points, curves, intersecting curves and closed curves are disposed, and accordingly the marker for positioning indicates a characteristic point of the image of object
25 for calibration presented in the finder in a state in which the relative positions of the photographing apparatus and the object for calibration are

appropriately set.

20. The finder apparatus according to claim 19,
wherein the characteristic point includes a central
point of a pattern of the object for calibration.

5 21. The finder apparatus according to claim 19,
wherein the characteristic point includes a joint
between the surfaces of the object for calibration.

22. The finder apparatus according to claim 19,
wherein the characteristic point includes
10 an arrangement of characteristic surface attribute
of the object for calibration.

23. A marker presentation member comprising one
of:

a member through which a visible light is
15 transmitted and on which a marker for positioning is
partially disposed to set relative positions of
a photographing apparatus and an object for calibration
including one of a known shape and surface attribute;
and

20 a member including the marker for positioning,
wherein

the one of the member on which the marker for
positioning is disposed and the member including
the marker for positioning is disposed on an optical
25 path of a light which guides the image of the object
for calibration into the operator's eyes, when
photographing the object for calibration in order to

acquire parameters of a photographing optical system of the photographing apparatus.

24. A method for presenting a marker for positioning for calibration photography, comprising:

5 presenting an image of an object for calibration in a finder which guides the image photographed by a photographing apparatus into operator's eyes so as to be visually recognizable by an operator, when photographing the object for calibration whose one of
10 shape and surface attribute is known in order to acquire parameters of a photographing optical system of the photographing apparatus; and

 presenting a marker for positioning to set relative positions of the photographing apparatus and
15 the object for calibration in the finder so as to be visually recognizable by the operator.

25. A finder apparatus which is used together with a photographing apparatus, comprising:

 a finder for presenting an image of a subject so
20 as to be visually recognizable by an operator; and

 positioning marker presentation means for presenting a marker for positioning for setting relative positions of the photographing apparatus and an object for calibration to the finder so as to be
25 visually recognizable by the operator, when the object for calibration including at least one of a known shape and a known surface attribute is photographed to

acquire a parameter of a photographing optical system
of the photographing apparatus.